


## N5-3116-LS-V2 – 16+2ch AHD/TVI Stand-Alone Hybrid DVR



**Hybrid AHD/TVI DVR**

**H.265+**

**UTC**

**CVBs**

**VGA**

**HDMI**

### Features :

- **H.265+** Compression – saving 50% HDD space
- Stable & Economical Linux base
- **Individual channel** auto detect :
  - **Analog** (960H) @Real-time 25fps
  - **AHD/TVI 720p Lite** @25fps
  - **AHD/TVI 720p** @12fps
  - **AHD/TVI 1080p Lite** @12fps
- Support **2ch IP Camera** 2~5MP
- **Analog CH can switch to IP**
- Full HD 1080p HDMI & VGA output
- **P2P, CVBs** output, USB2.0 x2
- **UTC** Camera OSD Control
- 16ch Simultaneous Playback
- Support 1HDD (Max. 8TB)
- Simultaneous User Login : **10**

### SPECIFICATION

Model	N5-3116-LS-V2
Channel	16 Coaxial + 2 IPC
Recording	WD1(960x676), 720p Lite (1320x540) @25fps/ch 720p(1320x1080), 1080p Lite (1920x540) @12fps/ch
Bandwidth	16 Mbps in / 80 Mbps out
Video Out	1xVGA, 1x Full HD 1080p HDMI, CVBs
Audio	1ch Audio in / 1ch Audio out
Storage	1 SATA HDD (up to 8TB)
Network	10/100 self adaptive RJ45 Ethernet port
Working Environment	-10° ~ +50°C, 10~90% Humidity
Power	12VDC, <10W w/o HDD (2A Adapter Included)
Dimension	225(W) x222(D) x 42(H)mm, 2.0kg w/o HDD